

AIGNER – Frontlinkage & Front PTO:

AIGNER frontlinkages and front PTO's are quality products – since 1981 we have been developing and manufacturing front systems in our factory.

Our products have over the years, proven their reliability over and over again – even under most extreme conditions. Our numerous loyal customers, some of them with whom we have an association of over 25 years, are the best proof!



Available for all series



Steering angle and the front axle oscillation completely maintained!



Your LANDINI-dealer:

All information and pictures are approximate and non-binding
Subject to technical alterations!

Technical Data	ALPINE 65-85	POWERFARM 60-105	VISION 85-105	LANDPOWER 125-185 TDI	REX 60-105 F/GE/GT
Powerlift cat.	cat. 2	cat. 2	cat. 2	cat. 2	cat. 1
Lifting force at link hook	23 kN	27 kN	27 kN	40 kN	15 kN
Double acting lifting cylinders	on request	on request	on request	standard	on request
Link hooks	Walterscheid Kat. 2	Walterscheid cat. 2	Walterscheid cat. 2	Walterscheid cat. 3L	Walterscheid cat. 1
PTO rotational speed	1000 rpm				
Direction of rotation	Clockwise in driving Direction				
PTO shaft profile	DIN 9611-1 3/8"				



Rupert Aigner GmbH • Mechanical Engineering
Hofstetten 7 • D-84431 Rattenkirchen/Germany
Tel.: +49 (0) 80 82/52 31 • Fax: +49 (0) 80 82/80 30
eMail: info@aigner-maschinenbau.de
Internet: www.aigner-maschinenbau.de

Frontlinkage & Front PTO



for LANDINI - Tractors

Robust Design
Sophisticated
Technology
Best Quality!



AIGNER – Frontlinkage & Front PTO:

Well proven since 1981!



Completely integrated system

Frontlinkage:

- Robust and sophisticated design conceived for the heaviest of accessory equipment and long operating hours
- Optimally adapted and designed to integrate with your LANDINI-tractor
- Highly stable due to frame up to clutch bell housing
- Steering angle and ground clearance completely maintained
- Lower links standardly equipped with Walterscheid link hooks
- As a standard, lifting arms can be folded up – without using a tool – and taken off
- Enhanced pendulum balance for the best ground adjustment of your front equipment – can be interlocked without tools
- all bearings and pivots can be greased
- standard tow bar clevis and spindle top link
- simple, quick assembly!



Lower links fold inward diagonally - optimum in case of the combination frontlinkage + front loaders!



Absolute ground clearance!



Stable frame up to clutch bell housing - Uninhibited front axle oscillation

Front PTO:

- unit completely integrated to your tractor
- designed for the heaviest of long-term loads – transfer of full motor power is easily possible!
- hydraulic front PTO clutch for a smooth and gentle start-up of your front devices
- can be activated and deactivated with the push of a button
- simple, quick assembly – front PTO can also be retrofitted later at any time!

Accessories:

- Quick coupling triangle cat. 2 with roller
- additional headlight H4, dimmable
- Accumulator for absorption
- Multivalve: double acting – single acting – locked (Transit support)
- Bracket for mower depth restriction-chain kit
- additional hydraulic connections in front



frontlinkage and PTO for a compact unit



activate with toggle switch



Holder for top link - Standard for all types



Attachment frame for tractor net weight 3-point attachment or for quick coupling triangle